

Industrial Motherboards for OEM/ODM

ONYX EMB-H81B

Thin Mini-ITX Embedded Motherboard with 4th Generation Intel® Core™ iSeries Processor



Features

- 4th Generation Intel® Core™ i Series 22nm Processor, Intel® H81
- DDR3 1333/1600 MHz SODIMM x 2, Up to 16 GB
- Dual Independent Display: LVDS, VGA, HDMI, DP
- SATA 6.0 Gb/s x 2, SATA 3.0 Gb/s x 1
- USB 3.0 x 2, USB 2.0 x 6
- PCI-E2.0 [x1] x 1, Full-size Mini-Card (mSATA) x 1, Half-size Mini-Card x 1
- 12V~24V DC Wide Range Voltage Power Input



Specifications

System

Processor	4th Generation Intel® Core™ i Series 22nm LGA1150 socket Processor, Max. 65W, TDPs
Chipset	Intel® H81
Memory	DDR3 1333/1600 MHz SODIMM x 2, Up to 16GB, Non-ECC, Dual-channel memory architecture(flat type)
I/O Chipset	NCT6791D
Ethernet	Realtek® PCIe Gb LAN 8111G x 2
Audio	Realtek® ALC887
TPM	Infineon SLB9635 TT 1.2
Expansion Slots	PCIe [x1] x 1, Full-size Mini-Card (mSATA default) (PCIe+USB optional)x 1, Halfsize Mini-Card (PCIe+USB) x 1
BIOS	64 M bit Flash ROM, AMI BIOS
H/W Monitor	Temperature Monitor on CPU/Chassis, Voltage Monitor on Vcore/5V/12V, Fan Monitor on CPU/Chassis
WatchDog Timer	1~255 steps by software program
Smart Fan Control	CPU Chassis Fan (Fanless)
Wake on LAN/ PXE	Yes (WOL/PXE)
Power State	S3, S4, S5

Graphics

Graphics Chipset	Intel® HD Graphics
Graphics Multi Display	VGA+HDMI, VGA+DP, VGA+LVDS, HDMI+DP, HDMI+LVDS, DP+LVDS
VGA	Up to 1920 x 1200 @60 Hz
DVI	—
HDMI	Up to 4096 x 2160 @24 Hz / 3840 x 2160 @60 Hz, with Digital Audio
Display Port	Up to 4096 x 2160 @24 Hz / 3840 x 2160 @60 Hz, with Digital Audio
LVDS	Up to 1920 x 1200 @60 Hz, dual-channel 18/24-bit
eDP	—
Backlight Control	Voltage/PWM

Environment / Power / ME

Battery	Lithium battery
Power Requirement	12-24V DC (wide range:12V-5%~ 24V+10%)
Operation Temp.	32°F ~ 140°F (0°C ~ 60°C)
Storage Temp.	-40°F ~ 185°F (-40°C ~ 85°C)
Operation Humidity	0% ~ 90% RH, non-condensing
Certificate	CE & FCC
Form Factor	Mini-ITX: 6.7" x 6.7" (170mm x 170mm)
Weight	1.1 lb (0.5 Kg)
MTBF (Hours)	288,500

Rear Panel I/O Ports

USB	USB 3.0 x 2, USB 2.0 x 2
Display I/O	HDMI x 1, DP x 1
Audio I/O	Mic-in x 1, Line-out x 1
LAN I/O	LAN (RJ-45) port x 2
Serial Port	—
PS/2 Port	—
Others	DC Jack x 1

Internal I/O Connectors

Storage	SATA3 (6.0Gb/s) x 2, SATA2 (3.0Gb/s) x 1, SATA power connector x 1, Full Size Mini-Card (mSATA) x 1
USB	USB 2.0 (2 x 5-pin, 2.00mm) x 3 ports support additional 6 USB (2 colay with Mini-Card)
Display I/O	VGA x 1, LVDS connector x 1, LVDS 3.3V /5V jumper x 1, LCD DC / PWM mode jumper x 1, LCD backlight connector (inverter) x 1, LCD backlight 12V /5V jumper x 1
Audio I/O	AAFP x 1, Speaker x 1
Serial Port	Boxer header for COM (RS-232) x 1, Boxer header for COM (RS-232/422/485) x 1
PS/2 Port	PS/2 Keyboard Mouse 6 PIN Connector x 1
Parallel Port	—
DIO	Digital I/O header x 1
FAN	4-pin CPU Fan connector x 1, 4-pin Chassis Fan connector x 1
Power	12V AUX Power Connector x 1, AT/ATX mode select jumper (optional) x 1
Others	Front Panel connector x 1, Chassis Intrusion x 1, Buzzer onboard (pin header) x 1, CMOS jumper x 1
OS Support	Windows® 10 64-bit, Windows® 7 32/64-bit, Windows® 8 32/64-bit, Linux Fedora